Suarez, Caesar (ISD) From: Suarez, Caesar (ISD) Sent: Friday, June 10, 2016 3:58 PM 'ieff@cms-miami.com'; 'dhcfla@bellsouth.net'; 'agkr1@mac.com'; To: 'gbruce@eptasolutions.com'; 'info@fasttransatm.com'; 'mario.e@c-global.com'; 'export@np-supply.com'; 'antonio@pemica.com' Johnson, Laurie (ISD); Martin, Marcia (ISD); White, Lourdes (ISD); Castro, Angel (ISD); Cc: Etienne, Eddy (ISD); Escalante, Jhonnatan (ISD); Fussell, Jacqueline (ISD); Hines, Patrick (ISD) Subject: RE: AAA-06-09-2016-D Verification of Availability, SBE/Goods & Services Attachments: aaa-06-09-2016-d-project-package.pdf.pdf Good Afternoon, Project Number: AAA-06-09-2016-D Project Title: **Food Service Equipment & Installation** SBD is in the process of placing a small business measure on the subject project but we need your help. Please review the information below and respond accordingly, ensuring that all applicable questions are answered. The deadline to respond is 4:00 PM, MONDAY, June 13, 2016. AAA-06-09-2016-D will be for procurement and installation of food service equipment. In addition to the attached specifications, vendors are required to comply with the following additional specifications below: This will be a one-time purchase Please note that the number reflected in the "ETD" column is in days and is inclusive of the lead time required to procure the equipment Please review the attached document and advise if your firm can provide the item(s) requested by placing a check mark next to each item in which your firm is able to provide. Name of Firm: SBE/GS Certification #:

PLEASE REMEMBER THAT YOUR PARTICIPATION IN THE AVAILABILITY TO PROPOSE PROCESS IS VITAL IN ORDER FOR SBD

Email:

Owner's Name: _____ Contact Person: _____

Date: _____ Contact #: _____

Caesar Suarez

SBD Capital Improvement Project Specialist Small Business Development Division Miami-Dade County Internal Services Department 111 NW 1st Street, 19th Floor, Miami, FL 33128 Cffice: (305) 375-3141 Fax: (305) 375-3160

TO PLACE SMALL BUSINESS MEASURES ON CONTRACTS.

Email: <u>caesars@miamidade.gov</u>

Connect With Us on <u>Twitter | Facebook</u> | <u>Instagram</u>



"Help stimulate Miami's economy by supporting Small Businesses"

RFI Line Items

ECPU: ESTIMATED COST P/UNIT

PMP: POTENTIAL MINIMUM PURCHASE

PAP: POTENTIAL ANNUAL PURCHASE

PF; PURCHASE FREQUENCY

ETD: ESTIMATED DELIVERY TIME

TILTING SKILLET, GAS - Braising Pan, Gas, 40-gallon capacity, 46" wide open base, manual tilt, 9" deep stainless steel pan with gallon markings, pouring lip & removable strainer	FLOOR TROUGH - Floor Trough, 24" x 72", subway-style stainless steel grating, 6"Deep 14/304 stainless steel all-welded drain pan with anti- splash design	WATER FILTRATION SYSTEM - FX Water Filter System, single 20" sump, (1) CTOS-20 cartridge with IsoNet®, 30,000 gallon capacity, 3 gpm, 0.5 micron sediment and chlorine, taste, odor reduction, scale inhibition	H PS! WATER CONNECTORS & FITTINGS - Dormont HI-PS(® Water Connector Hose, 3/4" dia 80" long, overed with stainless steel braid, brass twoway Quick Disconnect ocupling, within the lifetime warranty	SAFETY SYSTEM MOVEABLE GAS CONNECTOR - Dormont Blue Hose M Moveable Gas Connector Kit, 1" inside dia48" long, covered with stainless steel braid, coated with blue antimicrobial PVC	COMBI OVEN - Combitherm® CT PROformance™ Combi Oven/Steamer, gas, boilerfree, floor model with roll-in cart, (20) non- tilt support rails, (20) 18" x 26" full size sheet or (40) 12" x 20" full size hotel pan (1/1 GN) capacity, PROtouch control with steam	HAND SINK - Hand Sink, wall model, 14" wide x 10" front-to-back x 5" deep bowl, 20 gauge 304 series stainless steel, 7-3/4" high side splashes, with splash mounted faucet, wall bracket, NSF, cCSAus	TEM
Vulcan	Eagle Group	OptiPure	Dormont Manufacturing	Dormont Manufacturing	Alto-Shaam	Advance Tabco	ALK.
VG40	ASFT-2472-SG	FXI-12	W75B2Q60	16100KIT2S48	CTP20-20G	7-PS-66-2X	MER PARTS
8	J		1	10		3	ECPU MIN QT
	1	1					PAP PAP
-	-3				• ·	.	10 10 2P
28	28	29 88		:	28	28	E10
spring assist cover with drip edge, pan holder, thermostatic control, includes L faucet bracket, electric ignition, 12" stainless steel legs with adjustable flanged feet, 120,000 BTU	accommodates up to a 4"Diameter pipe, includes stainless steel removable perforated basket	for use with ice makers (up to 1,500 lb. cuber/2,000lb. flaker), coffee makers, steamers and combi ovens, NSF (160-50110)		1 SnapFast® QD. 2 Swivel MAX®, 1 full port valve, coiled restraining cable with hardware, 295,000 BTU/hr minimum flow capacity, limited lifetime warranty	venting, single point removable probe, CombiClean PLUS™ with (5) cleaning levels, CoolTouch3™ glass window, door hinged right, high efficiency LED lighting, stainless steel construction, seismic legs, 266,000 BTU, EcoSmar8, oULus, UL-EPH, ANS//NSF 4, CE, IP X5, Gastec, 120v/60/1-ph, 13.6 amps, 1.7kW, 14 AW/G, NO cord or plug, standard		DETAILS

sp 'N cu.in. rum ritch	EQUIP STAND FOR CHARBROILER - Equipment Stand, universal, 37" W × 24" + 1/2" mairine edge, undershelf, stainless steel, 5" casters	CHARBROILER - Achiever Charbroller, countertop, 36", (6) 17,000 BTU cast iron burners, infinite heat control valves, fully welded chassis, (1) drip tray	EQUIP STAND FOR COUNTERTOP GRIDDLE - Equipment Stand, universal, 49" W x 24" H, 1/2" marine edge, undershelf, stainless steel, 5" casters	COUNTERTOP GRIDDLE - Heavy Duty Griddle, countertop, gas, 48° W x 24" D cooking surface, 1" thick polished steel griddle plate, embedded mechanical snap action thermostat every 12"	SAFETY SYSTEM MOVEABLE GAS CONNECTOR - Dormont Blue Hose I'M Moveable Gas Connector Kit, 1-1/4" inside dia, .48" long, covered with stainless steel braid, coated with blue antimicrobial PVC.	CASTERS FOR HD RANGE - Casters (set of 4)	HEIGHT RISER FOR HD RANGE - Single deck height riser, no shelf, non overlapping, 36"	PRESSURE REGULATOR FOR HD RANGE - 1-1/4" NPT pressure regulator (Natural gas)	HD RANGE, 36", 6 OPEN BURNERS - V Series Heavy Duty Range, gas, 36", (6) 33,000 BTU open burners, cast iron grates, convection oven, stainless steel front	FRYER - Fryer, gas, 21" W, free- standing, 85-90 lb, capacity, millivolt thermostat controls, twin baskets,	CASTERS FOR CONVECTION OVEN - 6" Casters in lieu of legs	CONVECTION OVEN - Marathoner Gold Convection Oven, gas, double deck, bakery depth, electronic ignition, solid state controls, interior lights	VALVE FOR TILTING SKILLET - 2" draw-off valve, left front straight with strainer (pan support not available on 30-gallon)	WSHDWN DOUBLE FOR TILTING SKILLET - Pantry Deck Mount Faucet, with backflow preventer, 16" add on faucet, washdown hose, wall hook, NSF and Lead Reduction Compliant
Carter-Hoffmann :	Vulcan	Vulcan	Vulcan	Vuican	Dormont Manufacturing	Vulcan	Vulcan	Vulcan	Vulcan	Vulcan	Southbend	Southbend	Vulcan	Vulcan
CNH18	STAND/C-36	VACB36	STAND/C-48	MSA48	16125KIT2S48	RR4	V36ST22	PRESREG-NA11/4	V6B36C	1GR85M		GB/25SC	BPDOV-1	DBPTYTS
-				1	1				1	3	2	2	2	2
		.		: : : . →	: : -	_	-1	_				ے	- -	-
28	28		28		28	28	28	28	28	28	28	28	28	28
integrated collection pan, includes (2) stainless steel food bay dividers, forced-air heating system, polycarbonate rail on front, stainless steel construction, 1" rubber feet, cLLus, NSF, 120v/60/1-ph, 1820 watts, 15.1 amps, NEMA 5-20P, standard	Item for Charbroller, Vulcan, Model #VACB36	stainless steel front, sides & top trim, backsplash & grease trough, 4" adjustable legs, 102,000 BTU, CSA, NSF	Item for Countertop Griddle, Vutcan, Model #MSA48	millivolt pilot safety, manual ignition, low profile, stainless steel front, sides, front grease trough, 4" back & tapered side splashes, 4" adjustable legs, 108,000 BTU, CSA, NSF	SnapFast® QD, 2 Swivel MAX®, 1 full port valve, colled restraining cable with hardware, 449,000 BTU/hr minimum, limited lifetime warranty	Item for HD Range, Vulcan, Model #V6B36C	"Item for HD Range, Vulcan, Model #V6B36C	item for HD Range, Vulcan, Model #V6B36C	front top ledge, sides, base, burner box & stub back, 6" adjustable legs, 230,000 BTU, CSA, NSF	stainless steel cabinet and fry tank, adjustable casters (2 swivel locking & 2 non-locking), 150,000 BTU, CSA, NSF	Item for Southbend, Model #GB/25SC	includes (5) racks per deck, stainless steel front, sides, top, rear jacket & 6" legs, 180,000 BTU, CSA, NSF, (2) 120v/60/1-ph, 7.9 amps, NEMA 5-18P, standard	Item for Tilting Skillet, Vulcan, Model #VG40	Item for Titting Skillet, Vulcan, Model #VG40

	28		-3				TKSS-3012	Advance Tabco	WORK TABLE - Work Table, per /
	. 28		<u> </u>		10		C2436C	Centaur	WIRE SHELVING - Centaur® Shelving, wire, 36"W x 24"D, chrome, NSF
	28				. ப		C2430C	Centaur	WIRE SHELVING - Centaur® Shelving, wire, 30"W x 24"D, chrome, NSF
	28		is		- С	1	C2454C	Centaur	WIRE SHELVING - Centaur® Shelving, wire, 54"W x 24"D, chrome, NSF
Item for Roll-in Blast Chiller, Atto-Shaam, Model	28		- 					Alto-Shaam	ELECTRICAL FOR ROLL IN BLAST CHILLER - 115/208-230v/60/3-ph, 16.0 amps, 3.68 kW, 5 wire direct connection, no cord or plug
quick freeze soft-chill hard-chill and holding modes, automatic defrost cycle, with rack (40) full-size pan capacity, stainless steel interior and exterior, (4) adjustable legs. cULus, NSF	28		_				QC2-100	Alto-Shaam	ROLL-IN BLAST CHILLER - Quickchiller ⁷⁶ Blast Chiller, roll-in, self-contained with dual refrigeration systems, touch control with (20) preset menu options, (3) product temp probes
item for Security Unit, Eagle Group, Model #2448C-X	22 80	·				J	2448C-X	Eagle Group	SHELF FOR SECURITY UNIT - Shelf, wire, 48"W x 24"D, patented Quad frust@ design, includes (4) pairs of split sleeves per shelf, 800 lbs. capacity, chromeplated finish, NSF (FLYER)
EAGLEgard® hybrid epoxy finish with MICROGARD® antimicrobial protection, (2) swivel & (2) swivel/brake 5" stem casters with poly tread, KD, NSF	28		_			1	CSC2448E	Eagle Group	SECURITY UNIT - Security Unit. mobile, 51-1/4"W x 27-1/4"D x 69"H, Depen wire construction with 2" x 2" mesh panels, (2) doors with hasps for padlock
polypropylene, one-piece, seamless double wall construction, 4" square legs, speckled gray, NSF	28					f	DRS480480	Cambro	DUNNAGE RACK - S-Series Dunnage Rack, slotted top, 3000 lb. load capacity, 21'D x 48"W x 12"H
	28				96		C74K	Centaur	POSTS FOR WIRE SHELVING - Centaur® Stationary Post, 74-5/8"H, with eveling both & cap, green epoxy
	28	<i>:</i>	. -		16 ::		C2436K	Centaur	WIRE SHELVING - Centaur® Shelving, wire, 36"W x 24"D, green epoxy, NSF
	28		<u> </u>		4	9	C2460K	Centaur	WIRE SHELVING -Centaur® Shelving, wire, 60"W x 24"D, green epoxy, NSF
	28		<u></u>				C2454K	Centaur	WIRE SHELVING - Centaur® Shelving, wire, 54"W x 24"D, green epoxy, NSF
	28	•	-4				C2448K	Centaur	WIRE SHELVING - Centaur® Shelving, wire, 48"W x 24"D, green epoxy, NSF
Full Specs provided at bid	28				1			Kolpak	WALK IN COOLER/FREEZER - Cooler Interior Dimensions: 9-0 1/2" × 21-0" × 8-2 1/4", Freezer Interior Dimensions: 9-0 1/2" × 6-2" × 7-10 5/8"
Finish for Reach-In Undercounter Freezer, True Food Service Equipment, Model #TUC-27F-LP-HC	28	-	→ .	J	· · · · · · · · · · · · · · · · · · ·	1		True Food Service Equipment	FINISH FOR REACH-IN UNDERCOUNTER FREEZER - 16 ga. Stainless steel top
1-1/2" diameter dual wheel castors, 31-7/8"H counter height, front breathing, R290 Hydrocarbon refrigeran, 1/3 HP, 115v/60/1, 5.0 amps, NEMA 5-15P, 7' cord.	28		_				TUC-27F-LP-HC	True Food Service Ti	REACH-IN UNDERCOUNTER FREEZER - Low Profile Undercounter Freezer, -10° F, (2) Shelves, stainless steel top & sides, clear coated aluminum interior with stainless steel floor, (1) stainless steel door

WORK TABLE - Work Table, 36"W x 24"D, 14 gauge 304 series stainless steel top without splash, 18 gauge stainless steel adjustable undersheif, stainless steel legs with adjustable stainless steel bullet feet, NSF	WORK TABLE - Work Table, per drawing	REACH-IN UNDER COUNTER REFRIGERATOR - Low Profile Undercounter Refrigerator, 33-38° F, (2) shelves, stainless steel top & sides, clear coated aluminum interior with stainless steel floor	PLANETARY MIXER - 200- 240/50/60/3 Mixer, with bowl, beater, whip, & spiral dough arm; US/EXP configuration	MEAT SLICER - Heavy Duty Meat Slicer, automatic, 13" CleanCut TM removable knife with removal tool, burnished finish, (3) stroke tengths, & (4) stroke speeds, removable meat grip assembly	WORK TABLE - Work Table, 96"W x 30"D, 14 gauge 304 series stainless steel top with 5"H backsplash, 18 gauge stainless steel adjustable undershelf, stainless steel logs with stainless steel steel NSF	CASTERS FOR WORK TABLES - Casters, 5" diameter, set of 4 (2 with brakes) with stainless steel legs for standard working height of 35-1/2"	WORK TABLE - Work Table, 72"W x 30"D, 14 gauge 304 series stainless steel by without splash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with adjustable stainless steel bullet feet, NSF	WORK TABLE - Work Table, 60"W x 30"D, 14 gauge 304 series stainless steel top without splash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with adjustable stainless steel bullet feet, NSF	(2) short "Ell" 1/2" NPT female x male WASTE VALVE FOR WALL/SPLASH MOUNT FAUCET - twist handle, 3-1/2" sink opening, 2" drain outlet	INSTALLATION KIT FOR WALL/SPLASH MOUNT FAUCET - (2) 1/2" NPT ripples, lock nuts and washers	WALL / SPLASH MOUNT FAUCET - Sink Mixing Faucet, 12" swing nozzle, well mounted, 8" centers on sink faucet with 1/2" IPS eccentric flanged female inlets, lever handles
Advance Tabco	Advance Tabco	True Food Service Equipment	Hobart	Hobart	Advance Tabco	Advance Tabco	Advance Taboo	Advance Tabco	T&S Brass	T&S Brass	T&S Brass
SS-243	TKSS-3011	TUC-27-LP-HC	HL400-1STD	HS7-1	X39-308	TA-25S-4	\$9-306	SS-305	B-3952	B-0230-K	B-0231
			_	1		11	N	o	2		
-		·*	<u> </u>	<u> </u>	٦		-	<u> </u>	-	<u> </u>	-
N 8	28	28	22 80	. 28	28	28	.: 22	28	28	28	28
		(1) stainless steel door, 1-1/2" diameter dual wheel castors, 31-7/8" counter height, front breathing, R290 Hydrocarbon refrigerant, 1/6 HP, 1151/60/1, 20 amps, 7" cord, NEMA 5-15P, cULus, NSF, CE, 1-1/2" diameter dual wheel casters, standard	Legacy Planetary Mixer. 1.5 hp. 40-qt. capacity. (3) fixed speeds, geardriven transmission, 20 minute timer, #12 taper attachment hub, manual bowl lift, bowl guard, stainless steel bowl. "B" beater, "D" whip, "ED" dough hook	removable meat grip assembly, removable ring guard cover, single action top mounted sharpener with Borazon ^{Tu} stones, manual lift lever, 1/2 hp motor, 5.6amps, 120v/60hz/1-ph, NSF cETLus			(6) TA-22 Square edge table	(6) TA-22 Square edge table	Item for Faucet, T&S Brass, Model # B-0231	Item for Faucet, T&S Brass, Model # B-0231	

FINISH FOR BACK BAR COOLER - Condensing unit cover finish: Proceedings of the Condensing	BACK BAR COOLER - Refrigerated Back Bar Cabinet, four section, 108"W, self-contained refrigeration, (33.5) cu.ft. internal volume, front vented, stainless steel top & sides, (4) hinged doors with locks, stainless steel interior	CASTERS FOR BACK BAR COOLER - Set of rollers (1-5/8"), for Page 2: 3', 4' & 5' models	DOOR FOR BACK BAR COOLER - Door type, second: glass with P stainless steel door frame	}	FINISH FOR BACK BAR COOLER - Condensing unit cover finish: Stainless steel	F (< 0	HEATED BANQUET CART - Cabinet, Mobile Banquet, insulated, two doors, with thermostatically controlled heat unit,	HEATED CABINET, MOBILE - Cabinet, Mobile Heated, with humidity, insulated, bottom-mount heater assembly, recessed pushipull handles, (11) sets of chrome plated wire universal angle sildes on 4-1/2" centers adjustable 1-1/2" centers	DISH CART - Poker Chip Dish Dolly, 26-5/8"W x 26-5/8"D x 31-15/16"H, adjustable, dish size 4-1/4" to 11-3/4", removable dividers & towers, two-handed access.	PAN RACK, BUN - Roil-in Pan Cart, 20 shelf pan trolley, 2-9/16" vertical spacing, fits 20-20E, 20-20G, 20- 20MW and QCZ-100, stainless steel construction, (4) casters (2 locking)	PAN CART, ROLL-IN - Roll-In Plate Cart, 84 plates capacity, 9-11/16" vertical spacing, fits 20-20E, 20-20G, 20-20MV and QC2-100, stainless sized construction, (4) casters (2 locking)	PAN RACK, BUN - Bun Pan Rack, standard, 70-1/4"H, 3" spacing, capacity (20) 18" x 26" bun pans, front loading, welded, heavy duty aluminum construction, 5" swivel plate caster, NSF	WORK TABLE - Work Table, 48"W x 24"D, 14 gauge 304 series stainless steel top without splash, 18 gauge stainless steel adjustable undershelf, stainless steel legs with adjustable stainless steel bullet feet, NSF
Perlick Corporation	Perlick Corporation	Perlick Corporation	Perlick Corporation	Perlick Corporation	Perlick Corporation	Perlick Corporation	Cres Cor	Cres Cor	Metro	Alto-Shaam	Alto-Shaam	Channel Manufacturing	Advance Tabco
	BBS108	63771A	-		:	BBS60	CCB-120A	H-135-WUA-11-R	PCD11A	5017976	5016480	401A	SS-244
	1		1	J				on on		N			. \$
	<u>.</u>					→		- -	-x		->	- -	
28	28	28	. 28	28	. 28	28	28	228	28	228	- 28	28	28
Finish for Back Bar Cooler, Perlick Corp, Model # BRS108	galvanized steel back. (2) vinyl-coated shelves per door, digital thermostat, automatic defrost, LED interior lighting, automatic evaporator condensate, includes floor drain, R134a, 1/3 HP, NSF, cULus, 120v/60/1-ph, 6.3 amps, NEMA 5-15P	Casters for Back Bar Cooler, Perlick Corp, Model # BBS60	Door for Back Bar Cooler, Perlick Corp, Model # BBS60	Door for Back Bar Cooler, Perlick Corp, Model # BBS60	Finish for Back Bar Cooler, Perlick Corp, Model # BBS60	(2) hinged doors with locks, stainless steel interior, galvanized steel back, (2) vinyl-coated shelves per door, digital thermostat, automatic defrost, LED interior lighting, automatic evaporator condensate, includes floor drain, R134a, 1/4 HP, NSF, cULus	capacity (120) 11" covered plates or (90) 11-3/4" covered plates or (60) 13" covered plates, stainless steel riveted, welded & finished, perimeter bumper	(4) 5" swivel casters (2) braked, anti-microbial latches, analog thermometer, aluminum construction, red dutch doors, 1920watt, CSA	recessed handles, 5" dia. swivel casters with neoprene wheels (two with brakes), chip-resistant polymer shell with Microban antimicrobial protection, aesthetic blue, vinyl dust/water splash cover, NSF				

peristalic metering pumps, removable vinyl- coated glass racks, metal divider with safety switch, 650W wash tank heater included, stainless steel construction, 6" adjustable legs, 120w/60/1-ph, 5.4 amps, NEMA 5-15P, cultus, UL-EPH	28		_				PKBR24	Perlick Corporation	GLASS WASHER - Underbar Glass Washer, batch rotary type, 24°W, low temperature chemical sanitizing, (720) 2-14° dia. glasses per hour, 10° maximum glass height, top mounted instrument panel, upper & lower wash arms.
item for Chemical Storage Cabinet, Perlick Corp, Model # 7057-3	-3						54965-1	Perlick Corporation	DRAIN SCREEN FOR CHEMICAL STORAGE CABINET - Drain Screen, for 1-1/2" drain socket
Item for Chemical Storage Cabinet, Perlick Corp, Model # 7057-3	28		_			1	924GN-LF	Perlick Corporation	FAUCET FOR CHEMICAL STORAGE CABINET - Lead Free Faucet with gooseneck spout, wall mounted
	28				. U .	1	7057-3	Perlick Corporation	CHEMICAL STORAGE CABINET - Chemical Storage Cabinet, 12° W, with sink less faucet, cabinet base with removable dump box, water tight pan, quick disconnect spray hose, stainless steel exterior & 6° backsplash
Item for Drainboard, Perlick Corp, Model # TS24	28				-	A	SR-SL24	Perlick Corporation	SPEED RAIL FOR DRAINBOARD - Single Speed Rail, 24"W, locking, factory installed
6" Backsplash standard	28				22		TS24	Perlick Corporation	DRAINBOARD - TS Series Underbar Drainboard, 24"W x 18-91(3"D, embossed top, 6"H backsplash, stainless steel legs with adjustable thermoplastic feet, stainless steel construction, NSF
Item for Ice Bin, Perlick Corp. Model # SS30IC10	28						TSSBDSGA	Perlick Corporation	SODA GUN FOR ICE BIN - TSS Series Soda Gun Filler Section, 6" wide depth to match series, designed for use with Wunder-Ban® and Schroeder America™ 8-14 product soda gun / manifold
Item for Ice Bin, Perlick Corp, Model # \$530iC10	28			8	-	4	SR-SL30	Perlick Corporation	SPEED RAIL FOR ICE BIN - Single Speed Rail, 30"W, locking, factory installed
Item for Ice Bin, Perlick Corp, Model # 'S\$30IC10	28		<u> </u>				BW-SS6-30	Perlick Corporation	UNDERBAR BOTTLE WELL FOR ICE BIN. with lee Chest Cover Assembly, 6- bottle capacity, 4-piece straintess steel sliding cover assembly, (3) black polypropylene bottle wells on each side
	28		<u> </u>				SS30IC10	Perlick Corporation	PASS-THRU ICE BIN - Service Station Ice Chest, with cold plate, 30°W, concealed 10-circuit cold plate, 144 lb. ice capacity, ABS top ledge, stainless steel front & sides, stainless steel legs with thermoplastic feet
Casters for Back Bar Cooter, Perlick Corp. Model # BBS108	28				. J		63771A-2	Perlick Corporation	CASTERS FOR BACK BAR COOLER - Set of rollers (1-5/8"), for 6 & 8' models
Door for Back Bar Cooler, Perlick Corp. Model # BBS108	28	-						Perlick Corporation	DOOR FOR BACK BAR COOLER - Door type, fourth: glass with stainless steel door frame
Door for Back Bar Cooler, Perfick Corp. Model # BBS108	28		_					Perlick Corporation	DOOR FOR BACK BAR COOLER - Door type, third: glass with stainless steel door frame
Door for Back Bar Cooler, Perlick Corp, Model # BBS108	28		_					Perlick Corporation	DOOR FOR BACK BAR COOLER - Door type, second: glass with stainless steel door frame
Door for Back Bar Cooler, Perlick Corp, Model # BBS108	28							Perlick Corporation	DOOR FOR BACK BAR COOLER - Door type, first: glass with stainless steel door frame

							Totals	
Receive, uncrate, assemble and set in place for final connections	O)							CUSTOM INSTALLATION -
	Øi .	-		J	1			CUSTOM INSTALLATION - REFRIGERATION
stainless steel construction (28-13/16" x 16-13/16" cutout required)	28	: :			2	RDP18X30	Perlick Corporation	DRIP TROUGH - Drip Tray Trough, drop-in, 30"W x 18"D, for service station, (2) removable glass racks,
Item for Hand Sink, Perlick Corp. Model # TS12HSN	28		_			924GN-LF	Perlick Corporation	FAUCET FOR HAND SINK - Lead Free Faucet with gooseneck spout, wall mounted
C-fold paper towel dispenser on front apron, sound deadened underside, (1) 8-1/2" standpipe, 1-1/2" NPS male drain, stainless steel construction, stainless steel legs with adjustable thermoptastic feet, NSF	28		-			TS12HSN	Perlick Corporation	HAND SINK - TS Series Underbar Hand Sink Unit, free standing, 12"W x 22.14"D, 6" backsplash, 10" wide x 14" front-to-back x 9-1/4" deep sink, 4" O.C. splash mount faucet holes, 16 oz. pump soap dispenser